

PRODUCT SPECIFICATIONS

Wink is a clear high-gloss coating that creates a high performance, write-and-erase finish when applied to any paintable surface.

| | |
|---------------------------------|---|
| Kit contents | Part A: low odor, milky white, nonpigmented liquid emulsion Part B: pale yellow polymer hardener with slight odor |
| Coverage | Kits cover approximately 50, 100, or 200 square feet of surface area in a single coat |
| Characteristics | <ul style="list-style-type: none">—Clear finish eliminates limitations of a whiteboard, allowing any color to show through—Fast drying, high-gloss, waterbased formula covers in one coat without need for primer—Low Volatile Organic Compound (VOC) content of less than 50 grams per liter—Durable, long-lasting surface with 10,000+ scrub cycles and excellent stain removal—Class A rated for fire safety in accordance with ASTM E84; classified as insignificant flammability hazard by the Hazardous Material Identification System |
| Applications | Apply with a roller over smooth non-porous painted surfaces including drywall, marker board, chalkboard, metal, and glass, as well as smooth vinyl wallcovering. Opening, mixing, and installing Wink should be done by a professional installer, in accordance with the <i>Application Instructions</i> . |
| Preparation | Surface should be dry, prepared to Level 5 smoothness, and free of grease, mildew, and any imperfections. Spray application of primers/sealers and base coat of paint preferred. Scuff sanding recommended for high gloss surfaces. |
| Pot / Shelf Life | 1 hour open time / 6 month shelf life, providing product is not opened and is properly stored |
| Cure time | Surface is useable after four days |
| Environmental attributes | <ul style="list-style-type: none">—Free of formaldehyde, harmful carcinogens, chromium, lead, and mercury—Low VOC content of <50 g/L meets Green Seal™ standards for paints and coatings—Qualifies for contribution to LEED v4 for Low Emitting Materials—Meets or exceeds environmental criteria for non-flat coatings according to the U.S. Environmental Protection Agency, U.S. Green Building Council, Canada Green Building Council, South Coast Air Quality Management District, and the California Air Resources Board—More writing surface with far less environmental impact than a whiteboard |
| Writing/Drawing | Most new standard dry erase markers, in any color, can be used on the Wink surface. |
| Cleaning | For daily erasing and cleaning use a clean microfiber or dry-erase cotton cloth. Periodically, use a damp microfiber cloth or disposable wipes to maintain surface. |
| Warranty | 10-year limited warranty from date of shipment |
| Manufacturer | Innovative Chemical Products |
| Cost | 50 sq ft Kit: \$145; 100 sq ft Kit: \$235; 200 sq ft Kit: \$440 |