



© 2024 Wolf-Gordon Inc. All Rights Reserved

Lerida
COMMODORE

Category: Upholstery

Material: Polyurethane

Physical Properties

Content: 95% Polycarbonate, 5% Silicone

Finish: Graffiti-proof, TPE-encapsulated stain resistant, impermeable treatment

Backing: Polyester Knit

Width: 54"

Weight: 19.00 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Breaking Strength: ASTM D751 - Warp: 182 lbs; Weft: 126 lbs

Abrasion: 100,000* double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 15.0 lbs; Weft: 11.0 lbs

Seam Strength: ASTM D751- Warp: 67.8 lbs; Weft: 65.3 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 200 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Hydrolysis Resistance: ISO 1419 - 15 weeks

Sustainability

Free of conflict minerals, flame-retardant chemicals, heavy metals, PFC/ PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)

Printed with solvent-free inks

*Actual Wyzenbeek test results: 300,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.