



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Velveteen
CALYPSO

Category: Upholstery

Material: Polyester/Polyester Blend

Physical Properties

Content: 100% Polyester

Finish: Spill- and stain-resistant treatment

Backing: Acrylic

Width: 55"

Weight: 15.48 oz per linear yards

Performance

For Indoor/Outdoor Use: Antimicrobial, mildew resistant, and water repellent

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Breaking Strength: ASTM D5034 - Warp: 237 lbs; Weft: 187 lbs

Abrasion: 100,000* double rubs, Wyzenbeek; 100,000 cycles, Martindale

Tear Strength: ASTM D2261 - Warp: 23.0 lbs; Weft: 24.0 lbs

Pilling: ASTM D3511 (Brush Pill) - Grade 5

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 1200 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of conflict minerals, heavy metals, PFC/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents, PFAS

*Actual Wyzenbeek test results: 200,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.