



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Kinetic Smoke

Category: Upholstery

Material: Polyester/Polyester Blend

Physical Properties

Content: 100% Polyester

Width: 54"

Weight: 20.80 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -
Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 3

Breaking Strength: ASTM D5034 - Warp: 323.1 lbs; Weft: 119.3 lbs

Seam Slippage: ASTM D4034 - Warp: 64.3 lbs; Weft: 48.3 lbs

Abrasion: 72,000 double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 53.0 lbs; Weft: 53.0 lbs

Pilling: ASTM D3511 (Brush Pill) - Grade 4

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours

Cleaning Code: W = Clean with only a waterbased cleaning agent

Sustainability

Free of conflict minerals, flame-retardant chemicals, heavy metals, PFC/
PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP),
solvents