WolfGordon 🖌




Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Maxton SPARROW

Category: Upholstery

Material: Polyester/Polyester Blend

Physical Properties

Content: 100% Polyester

Finish: GreenShield® spill- and stain-resistant treatment

Backing: Acrylic

Width: 54"

Weight: 21.98 oz per linear yards

Performance

Fire Rating: ASTM E84 (UnAdhered) Class A Flame Spread: 15 Smoke Developed: 65

Fire Rating: Passes NFPA 286

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 3

Breaking Strength: ASTM D5034 - Warp: 207 lbs; Weft: 272 lbs

Seam Slippage: ASTM D4034 - Warp: 85 lbs; Weft: 95 lbs

Abrasion: 78,000 double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 16.0 lbs; Weft: 34.0 lbs

Pilling: ASTM D3511 (Brush Pill) - Grade 4

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of halogenated flame retardants, heavy metals, PFC/PFOA/PFOS, solvents