



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Segment
SLATE

Category: Upholstery
Material: Acrylic/Acrylic Blend Sunbrella® Contract

Physical Properties

Content: 63% Acrylic, 37% Polyester
Finish: Spill- and stain-resistant treatment
Width: 54"
Weight: 14.98 oz per linear yards
Repeat: 17.04" H x 3.5" V

Performance

For Indoor/Outdoor Use: Antimicrobial, mildew resistant, and water repellent
Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC
Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4.5; Wet: Grade 5
Breaking Strength: ASTM D5034 - Warp: 346 lbs; Weft: 356 lbs
Seam Slippage: ASTM D4034 - Warp: 81.8 lbs; Weft: 73.2 lbs
Abrasion: 100,000 double rubs, Wyzenbeek
Tear Strength: ASTM D2261 - Warp: 67.3 lbs; Weft: 63.3 lbs
Pilling: ASTM D3511 (Brush Pill) - Grade 4
Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 2000 hours
Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of conflict minerals, flame-retardant chemicals, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)