



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Tallinn  
KUMQUAT

Category: Upholstery  
Material: Polycarbonate Polyurethane

Physical Properties

---

Content: 100% Polyurethane  
Finish: Inherently stain- and ink-resistant, liquid impermeable treatment  
Backing: Polyester Knit  
Width: 54"  
Weight: 20.00 oz per linear yards

Performance

---

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC  
Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5  
Breaking Strength: ASTM D751 - Warp: 109 lbs; Weft: 127 lbs  
Abrasion: 100,000 double rubs, Wyzenbeek  
Coating Adhesion: ASTM D751 - Warp: 8.8 lbs; Weft: 7.1 lbs  
Tear Strength: ASTM D2261 - Warp: 7.0 lbs; Weft: 6.3 lbs  
Seam Strength: ASTM D751- Warp: 59.9 lbs; Weft: 57.4 lbs  
Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 200 hours  
Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used  
Hydrolysis Resistance: ISO 1419 - 5 weeks

Sustainability

---

Low emitting-passes Cal 01350 standard (LEED EQ 4.2)  
Free of conflict minerals, heavy metals, PFC/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)  
Printed with solvent-free inks