



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

## Zigrino MINERAL

Category: Upholstery

Material: Vinyl

**Physical Properties** 

Content: 100% Vinyl

Finish: Spill- and stain-resistant treatment

Backing: Woven Polyester/Cotton

Width: 54"

Weight: 35.00 oz per linear yards

Repeat: 10.5" H x 10" V

## Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -

Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Breaking Strength: ASTM D751 - Warp: 68 lbs; Weft: 55 lbs

Abrasion: 100,000\* double rubs, Wyzenbeek

Coating Adhesion: ASTM D751 - Warp: 12.1 lbs; Weft: 8.9 lbs Seam Strength: ASTM D751- Warp: 70.9 lbs; Weft: 52.6 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 200 hours

Cleaning Code: W = Clean with only a waterbased cleaning agent; a

diluted bleach solution can be used

## Sustainability

Free of conflict minerals, flame-retardant chemicals, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents

Printed with solvent-free inks

<sup>\*</sup>Actual Wyzenbeek test results: 200,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.