



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

## Score

### INK

Category: Upholstery

Material: Polyester/Polyester Blend

#### Physical Properties

---

Content: 100% Polyester

Finish: GreenShield® ZERO, PFAS free, spill- and stain-resistant treatment

Backing: Acrylic

Width: 54"

Weight: 15.00 oz per linear yards

#### Performance

---

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4.5; Wet: Grade 5

Breaking Strength: ASTM D5034 - Warp: 163.1 lbs; Weft: 353 lbs

Seam Slippage: ASTM D4034 - Warp: 30.5 lbs; Weft: 86.5 lbs

Abrasion: 100,000\* double rubs, Wyzenbeek

Pilling: ASTM D3511 (Brush Pill) - Grade 5

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent

#### Sustainability

---

Free of conflict minerals, heavy metals, PFC/PFOA/PFOS, PVC, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents, PFAS

\*Actual Wyzenbeek test results: 190,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.