## WolfGordon 🖌



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

## Marlowe THRILL

Category: Upholstery Material: Polycarbonate **Physical Properties** Content: 100% Polyurethane Backing: Polyester Knit Width: 54" Weight: 25.00 oz per linear yards Performance Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -Passes NFPA 260/UFAC Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5 Breaking Strength: ASTM D751 - Warp: 121 lbs; Weft: 137 lbs Marine Applications: IMO FTP Code 2010 Abrasion: 100,000\* double rubs, Wyzenbeek Coating Adhesion: ASTM D751 - Warp: 13.6 lbs; Weft: 12.0 lbs Tear Strength: ASTM D2261 - Warp: 8.5 lbs; Weft: 8.2 lbs Seam Strength: ASTM D751- Warp: 72.7 lbs; Weft: 97.8 lbs Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 200 hours Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used Hydrolysis Resistance: ISO 1419 - 15 weeks Sustainability

Free of conflict minerals, heavy metals, PFC/PFOA/PFOS Printed with solvent-free inks

\*Actual Wyzenbeek test results: 200,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.