



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

**Marlowe**  
**SUMATRA**

Category: Upholstery  
Material: Polycarbonate

Physical Properties

Content: 100% Polyurethane  
Backing: Polyester Knit  
Width: 54"  
Weight: 25.00 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC  
Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5  
Breaking Strength: ASTM D751 - Warp: 121 lbs; Weft: 137 lbs  
Marine Applications: IMO FTP Code 2010  
Abrasion: 100,000\* double rubs, Wyzenbeek  
Coating Adhesion: ASTM D751 - Warp: 13.6 lbs; Weft: 12.0 lbs  
Tear Strength: ASTM D2261 - Warp: 8.5 lbs; Weft: 8.2 lbs  
Seam Strength: ASTM D751- Warp: 72.7 lbs; Weft: 97.8 lbs  
Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 200 hours  
Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used  
Hydrolysis Resistance: ISO 1419 - 15 weeks

Sustainability

Free of conflict minerals, heavy metals, PFC/PFOA/PFOS  
Printed with solvent-free inks

\*Actual Wyzenbeek test results: 200,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.