



© 2024 Wolf-Gordon Inc. All Rights Reserved

Normandy LIMESTONE

Category: Upholstery

Material: Polyester/Polyester Blend Supreen

Physical Properties

Content: 92% Polyester, 6% Polyurethane, 2% Silicone

Finish: Supreen PFAS-free, stain-resistant treatment with moisture barrier

Width: 54"

Weight: 22.00 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4.5; Wet: Grade 4.5

Breaking Strength: ASTM D5034 - Warp: 330 lbs; Weft: 145 lbs

Seam Slippage: ASTM D4034 - Warp: 87.5 lbs; Weft: 99.5 lbs

Abrasion: 100,000 double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 23.4 lbs; Weft: 49.7 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of conflict minerals, flame-retardant chemicals, heavy metals, PFC/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)

Printed with solvent-free inks