



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

**Esme**  
**EFFERVESCENT**

Category: Upholstery  
Material: Polycarbonate Polyurethane  
Physical Properties

Content: 100% Polycarbonate  
Finish: Stain- and ink-resistant treatment  
Backing: Woven Polyester/Cotton  
Width: 54"  
Weight: 20.00 oz per linear yards

Performance  
Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC  
Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5  
Breaking Strength: ASTM D751 - Warp: 128 lbs; Weft: 106 lbs  
Abrasion: 100,000\* double rubs, Wyzenbeek  
Coating Adhesion: ASTM D751 - Warp: 10.1 lbs; Weft: 6.8 lbs  
Tear Strength: ASTM D2261 - Warp: 9.6 lbs; Weft: 11.3 lbs  
Seam Strength: ASTM D751- Warp: 88.7 lbs; Weft: 92.0 lbs  
Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 200 hours  
Cleaning Code: S = Clean only with a water-free dry cleaning solvent; a diluted bleach solution can be used  
Hydrolysis Resistance: ISO 1419 - 7 weeks

Sustainability  
Free of flame-retardant chemicals, PFC/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents  
Printed with solvent-free inks

\*Actual Wyzenbeek test results: 150,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.