



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Felted Smudgy

Category: Wallcovering

Material: Acoustical

Physical Properties

Content: 100% Polyester

Width: 63"

Weight: 25.00 oz per linear yards

Hanging Information: Straight Hang, Random Match

Performance

Fire Rating: ASTM E84 (Adhered) and IBC Section 803.1.2 - Class A

Flame Spread: 5

Smoke Developed: 20

Fire Rating: ASTM E84 (UnAdhered) Class A

Flame Spread: 0

Smoke Developed: 95

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 4

Seam Slippage: ASTM D4034 - Warp: 227 lbs; Weft: 310 lbs

Abrasion: 40,000 cycles, Martindale

Pilling: ASTM D3511 (Brush Pill) - Grade 3

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Noise Reduction Coefficient: 0.2

Sustainability

Low emitting-passes Cal 01350 standard (LEED EQ 4.2)

Free of PVC