



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

## **Skye SKY 7003 Parch**

Category: Upholstery

Material: Tekloom®

### Physical Properties

---

Content: 88% Polyester  
12% Thermoplastic Elastomer

Finish: Tekloom® PFAS-free, graffiti-proof, impermeable treatment

Width: 54"

Weight: 20.00 oz per linear yards

### Performance

---

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -  
Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Breaking Strength: ASTM D5034 - Warp: 321 lbs; Weft: 270 lbs

Seam Slippage: ASTM D4034 - Warp: 74.5 lbs; Weft: 60.5 lbs

Marine Applications: IMO FTP Code 2010

Abrasion: 100,000\* double rubs, Wyzenbeek

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

### Sustainability

---

Free of conflict minerals, flame-retardant chemicals, PFAS/PFOA/PFOS, PVC, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), PFAS

Printed with solvent-free inks

\*Actual Wyzenbeek test results: 1,000,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.